

## The easily adhering and breathable surface protective roll

### Installing instruction

#### Application

**albert floorotex** is a breathable, easily adhering surface protective roll and is suitable for covering different kind of flooring like hardwood floor, laminate and ceramic floor.

#### Properties

- **Waterproof but still breathable** – water cannot go through and underlying moisture does not get trapped
- **Protects** – against scratches and other damage
- **Anti-skid** – mat cannot slip – no need for any tape at the sides
- **Very strong material** – does not tear
- **Reusable** – can be used several times

#### Installing instructions

- Turn-off floor heating before laying
- The rolls should be laid down with an overlapping on each side by about 10 cm (4 inches)
- Protect against direct solar radiation
- The areas to be covered must be dry underneath the breathable surface protective roll.
- The floor protective film cannot endure a permanent pressure of more than 100 kg/m<sup>2</sup> for more than 24 hours
- Waiting period for laying:
  - Follow the manufacturer's guidelines for complete curing times. Due to variable

site conditions, a site test should also be done to ensure floor is cured.

- Never use the mat earlier than 72 h after the final coat has been applied.
- Room temperature 10° – 25°C
- Allowable room humidity 50% – 60%

All the details included in this technical product information are based on our best knowledge and experiences. They do not represent a guarantee of certain properties. It is the responsibility of the processor to determine the suitability for a particular purpose through his own tests and trials. Should the adherent underside remain on the floor, we disclaim liability.

#### Important

The areas to be covered must not release any solvent vapours. No solvent vapours may be present on top of the areas to be covered. albert Bauprodukte can not ensure that the product can be used as suggested. Should the adherent underside remain on the floor, albert Bauprodukte disclaims liability.

Do not use on newly laid porous stone floors or earthenware slab.

In the rare case of a residue remaining on the surface after albert floorotex has been laid, simply remove the residue by gently wiping it away with a wet (use lukewarm water) kitchen cloth or rag, and if necessary, a small amount of hand soap.

albert floorotex is slightly adherent on the bottom. To avoid accidents the joints of the mat have to be taped down.

#### Technical data

|  | Value   | Norm   |
|--|---|--|
| Material   | PET fibres (recycled fibres), needled               |  |
| Form of reinforcement                                      | Top: breathable PP film as liquid barrier           |  |
| Underside  | Residue-free anti-slip adhesion                     |  |
| Weight   | 0.033 lbs per sq.ft<br>160g/m <sup>2</sup> (+/-10%) | DIN EN 29073-1                                   |
| Thickness  | 2.5 – 2.8 mm  | DIN EN ISO 9073-2                                |
| Thickness with 0.5 kpa load (approx. 50g/cm <sup>2</sup> ) | 1.52 mm (+/-10%)                                    | DIN EN ISO 9073-2                                |
| Dimensions   | 40" x 84' = 280 sq.ft<br>40" x 168' = 560 sq.ft     |  |
| Maximum longitudinal tensile strength                      | 120N/5 cm (+/-20%)                                  | DIN EN 29073-3                                   |
| Maximum transverse tensile strength                        | 115N/5 cm (+/-20%)                                  | DIN EN 29073-3                                   |
| Maximum longitudinal extension                             | 80% (+/-20%)  | DIN EN 29073-3                                   |
| Maximum transverse extension                               | 90% (+/-20%)  | DIN EN 29073-3                                   |
| Water vapour permeability of the film                      | 25g/m <sup>2</sup> /24h                             | EN 12572 climate C<br>RH 50/100 @ 23° C, Wet Cup |
| Value Sd of the film                                       | 1 m   |  |
| Water depth of the film                                    | > 6 m   | DIN 53886 (with support grid)                    |

These processing instructions may be invalid because of new findings or developments. The currently valid processing instructions are available at [www.albert.ch](http://www.albert.ch).

With purchasing the product, the customer accepts place of jurisdiction: 6060 Sarnen, Switzerland.