

PRODUCT INFORMATION

WINDOW SHIELD

Protect windows against mortar stains, stucco, over sprays, residue and more with the easy to apply Window Shield. Formulated never to leave a residue, this protective film is available in short, medium and long term protection, ranging from 45 days to 1 year. Start saving time and money on the job with this dependable window film.



Liquid Shield



Recyclable



FEATURES

- Self-adhering protective film for windows and glass
- Protects against oversprays, mortar stains and stucco
- No more scraping and cleaning damage to the glass
- Saves time, labor and money

APPLICATIONS

- Construction
- Remodeling
- Tuck Pointing
- Drywall
- Painting
- Temporary Protection



PRODUCT SPECIFICATIONS

Thickness	1.5 mil nominal (short term) 3.1 mil nominal (long term)
Film	Polyethylene w/UV Inhibitor (short term), PVC w/UV Inhibitor (long term)
Adhesive Type	Water-based Acrylic
Adhesion Level	8.5 oz/in (short term), 48 oz/in (long term)
Tensile Strength	2-3000 psi (short term), 5100 psi (long term)
Temperature (Ideal)	70° F
Humidity (Ideal)	50%
Elongation	300-400% (short term), 260% (long term)
Chemical Name	Acrylic PSA Tapes
Chemical Family	Acrylic PSA Polyethylene Film
Chemical Formula	Proprietary
Trade Name	Window Shield
Material Use	Surface Protection

AVAILABLE SIZES

W2B12600	Blue	12in x 600ft (30-45 days, 2pk)
W2B24250	Blue	24" x 250' (30-45 days)
W2B24600	Blue	24" x 600' (30-45 days)
W2C24600	Clear	24" x 600' (30-45 days)
W2C36250	Clear	36" x 250' (30-45 days)
W3C24600	Clear	24" x 600' (90-180 days)
W4B24330	Blue	24" x 330' PVC Long term (6mns -1yr)
W4B36330	Blue	36" x 330' PVC Long term (6mns -1yr)

INSTRUCTIONS

Peel back edge of Window Shield and begin to unroll. Press down edge at beginning of area to be covered so Window Shield adheres. Continue rolling onto area, applying pressure and smoothing down the film while doing so. Carefully cut end with a sharp edge. When finished, fold edge of the film back against the roll to use at a later time. Removal: roll up Window Shield and discard.

HANDLING AND STORAGE

Store at room temperature and keep out of direct sunlight exposure. If Window Shield is stored in extreme conditions over 95° F or below 40° F allow product to return to room temperature prior to use.

SAFETY

SDS sheets for Surface Shields products available by request.

The information in this document was obtained from sources which we believe reliable. The information is provided without any warranty expressed or implied regarding its correctness. We do not assume responsibility for loss, damage or expense in any way connected with the handling, storage, use or disposal of the product.

© 2016 Surface Shields, Inc. All rights reserved. Product names & attributes trademark of Surface Shields, Inc. where applicable.